

Microwaves & RF

DESIG 2005 Editorial Index

COMMERCIAL

- Top products of 2004 (*January*, p. 80)
- Wireless puts down medical roots (*September*, p. 33)
- Top products of 2005 (*December*, p. 94)

COMMUNICATIONS

- Measuring the costs of broadband services (*July*, p. 33)
- Broadband served by multiple technologies (*November*, p. 33)
- Emerging markets drive RF technologies (*December*, p. 33)
- NPR specification aids wireless system analysis (*December*, p. 53)

COMPONENTS

- Achieving high gain over broad bandwidths (*January*, p. 60)
- RLC components support higher-level designs (*February*, p. 33)
- Cascading amp stages for higher gain (*February*, p. 66)
- Dividers and terminations cut costs to 8 GHz (*February*, p. 102)
- Quad hybrids serve 450-MHz CDMA systems (*February*, p. 104)
- Analyzing 4:1 TLTs for optical receivers (*March*, p. 78)
- Broadband amps boost linear power to 26.5 GHz (*March Cover*, p. 92)
- Cables and connectors make microwave links (*April*, p. 33)
- Equalize gain in millimeter-wave amplifiers (*April*, p. 61)
- Design an E-phemt 4.9-to-6.0-GHz LNA (*April*, p. 80)
- Antenna modules demystify wireless designs (*April*, p. 108)
- Analyze circulator design equations (*May*, p. 68)
- Stable sources limit phase hits (*May*, p. 124)
- Reducing ADC quantization noise (*June*, p. 72)
- Slot boosts bandwidth of WLAN patch antennas (*June*, p. 86)
- Cables connect test gear to 18 GHz (*June*, p. 110)
- Capacitive loading shrinks mobile PIFAs (*July*, p. 56)
- Microstrip antennas guide satellite data transmissions (*July*, p. 68)
- Biconical antenna scans 4.8 to 5.8 GHz (*August*, p. 53)
- Gauge wideband LO noise in passive Tx/Rx mixes (*August*, p. 62)
- Wideband mixers hit high intercept points (*September Cover*, p. 98)
- Cable company doubles as connector supplier (*September*, p. 108)

Microwaves & RF

2005

Editorial Index

- Coax cables improve receiver performance (*September*, p. 110)
- Ceramic technology yields stable resonators (*September*, p. 114)
- Passive components benefit from materials advances (*October*, p. 33)
- Overlay inductor aids power amplifier match (*October*, p. 53)
- NLTLs push sampler products past 100 GHz (*October Cover*, p. 88)
- Rotary attenuators step 100 dB to 4.5 GHz (*October*, p. 102)
- "Disruptive" ceramic technology enables spectrum management (*October White Paper*, Part 1)
- Baluns shrink to tiny 0404 footprint (*November Cover*, p. 80)
- FCBs shrink systems from 8 to 40 GHz (*November*, p. 90)
- "Disruptive" ceramic technology stabilizes spectrum management (*November White Paper*, Part 2)
- Resistive loading enhances LNA stability (*December*, p. 64)

COMPUTER-AIDED ENGINEERING

- Model optical transmitters with a circuit simulator (*April*, p. 92)
- Software supports signal-integrity analysis (*May*, p. 130)
- Software shaves spurs in frequency planning (*June Cover*, p. 102)
- EM simulators reveal contents of crystal ball (*August*, p. 33)
- Design and verify a 50-W power amp (*October*, p. 76)
- Cluster computers speed EM simulation (*November*, p. 53)

CONFERENCES

- Microwave week returns to sunny California (*May*, p. 33)
- MEMS and models move forward at 2005 IEDM (*November*, p. 36)

DEFENSE ELECTRONICS

- Technology fills homeland-security gaps (*June*, p. 33)

DEVICES & ICs

- IC suppliers support growing WLAN arena (*January*, p. 33)
- RF modulator enable multicarrier transmitters (*April Cover*, p. 100)
- MESFET process yields MMIC Ka-band PAs (*May*, p. 96)
- Efficiently design and model MMICs with passive elements (*June*, p. 92)
- DDS IC initiates synchronized signals (*July Cover*, p. 76)
- High-power transistors focus on emerging applications (*July*, p. 40)
- InGaP gain blocks boost 0.1 to 6.0 GHz (*August*, p. 86)
- RF chip sets support 802.16d/e front ends (*August*, p. 88)

SYSTEMS & SUBSYSTEMS

- Laser-based system speeds PCB prototypes (*January Cover*, p. 74)
- Frequency synthesizers generate clean signals (*March*, p. 33)
- Design improves 4.3-GHz radio altimeter accuracy (*June*, p. 57)
- Synchronized synthesizers aid multichannel systems (*September*, p. 57)
- Tracking transmitter compliance testing (*September*, p. 70)
- Building wireless sensor networks (*September*, p. 78)
- Gauging limitations on DFD performance (*November*, p. 68)



TEST & MEASUREMENT

- Compare analyzers and meters for power tests (*January*, p. 50)
- Digital oscilloscopes capture 250 Msamples/s (*January*, p. 84)
- Surveying synthetic instruments for defense (*February*, p. 57)
- Checker reads cellular radiation (*February*, p. 76)
- Three-probe tuner tackles multiple tasks (*February Cover*, p. 90)
- Refinements revitalize variable delay lines (*February*, p. 110)
- Tackling SE testing on microwave cables (*March*, p. 55)
- Method validates SAR measurement systems (*March*, p. 68)
- Clock-recovery module sets low-jitter standards (*March*, p. 98)
- Method validates SAR measurement systems (*April*, p. 70)
- Digital scopes battle jitter with 100-GHz bandwidth (*April*, p. 110)
- Make ultrawideband OFDM transmitter measurements (*May*, p. 55)
- Improvements propel peak power meter (*May Cover*, p. 116)
- Scope and probe capture 40 Gsamples (*June*, p. 112)
- Synthetic instruments tackle military testing (*August Cover*, p. 78)
- Method measures device power and gain (*September*, p. 86)
- Characterize balanced devices with a VNA (*October*, p. 60)
- Test cables' "memory" saves component stress (*October*, p. 100)
- Eight-port VNA aids production testing (*October*, p. 106)
- Real-time spectrum analyzers show complex waveforms (*December*, p. 74)
- Portable VNA tests two ports to 6 GHz (*December Cover*, p. 88)

